

# NiTO II cleaning gun

The NiTO II spray gun is thermally insulated and has an adjustable spray angle, from narrow to wide (60°). Suitable for "heavy" applications with a water temperature of up to 90 °C and a flow rate of 40 l/min. It is equipped with 3/4" BSP female thread, and the operating lever is lockable to prevent unintended use.

## Technical Specifications

- Maximum pressure: 25 bar
- Maximum temperature: 90 °C
- Maximum flow: 40 l/min.
- Full linear flow control, from low to high
- Adjustment from narrow to wide spray pattern (60° angle)
- Trigger with on/off and lock function
- 3/4" BSP female thread inlet
- Can be connected to 1/2" or 3/4" hoses
- Weight: 700 g

Although all materials can handle temperatures up to 90 °C, special precautions are recommended if hot water is used. **The gun is not suitable for steam.**

The NiTO II comes standard with a nozzle with a capacity of 40 l/min. A separate set of nozzles is available for the gun. This allows you to increase or decrease the capacity of the gun. The separately available set contains nozzles with a capacity of 20 l/min, 30 l/min, 60 l/min and an Allen key. The part number is AK30210A0.

A swivel coupling on a gun improves user-friendliness and extends the life of the hose. See the "ball bearing swivels" page for more information.

Available model:



**AK30550A3**



**AK30210A0**

All article numbers in **bold** are available from stock.